



Freestanding Enclosed Series (FSE)

Output Pressure Range	Supply Voltage Max Amp Draw	Remote Monitoring & Connector	Part Number
0.5 - 15psig	120VAC 1.8 at 60hz 3.1 at 50hz	None	WDH2-FSE-15-120
		Ethernet RJ45	WDH2-FSE-15-120-ERM
		Voltage (0-10VDC) 3wire M12, w/ 1m cable flying leads	WDH2-FSE-15-120-OPM15V
		Current (4-20mA) 3wire M12, w/1m cable flying leads	WDH2-FSE-15-120-OPM15C
	240VAC 1.0 at 60hz 1.5 at 50hz	None	WDH2-FSE-15-240
		Ethernet- RJ45	WDH2-FSE-15-240-ERM
		Voltage (0-10VDC) 3wire M12, w/ 1m cable flying leads	WDH2-FSE-15-240-OPM15V
		Current (4-20mA) 3wire M12, w/1m cable flying leads	WDH2-FSE-15-240-OPM15C
0.5 - 30psig	120VAC 1.8 at 60hz 3.1 at 50hz	None	WDH2-FSE-30-120
		Ethernet- RJ45	WDH2-FSE-30-120-ERM
		Voltage (0-10VDC) 3wire M12, w/ 1m cable flying leads	WDH2-FSE-30-120-OPM30V
		Current (4-20Ma) 3wire M12, w/1m cable flying leads	WDH2-FSE-30-120-OPM30C
	240VAC 1.0 at 60hz 1.5 at 50hz	None	WDH2-FSE-30-240
		Ethernet- RJ45	WDH2-FSE-30-240-ERM
		Voltage (0-10VDC) 3wire M12, w/ 1m cable flying leads	WDH2-FSE-30-240-OPM30V
		Current (4-20mA) 3wire M12, w/1m cable flying leads	WDH2-FSE-30-240-OPM30C

Enclosure	Dimensions Weight Mounting	18.25" (W) x 9.5" (D) x 18.75" (H) (20.75" with handles) 44 lbs Free Standing
Power	Power usage Compressor Type	483 VA max Oil-less rocking piston 1/4 HP motor,
Output	Flow rate Maximum pressure Dewpoint:	1.4 cfm @ 1 psig Regulated = 0.5 - 15 psig and 0.5 - 30 psig 0° to -20°F
Environmental	Temperature rating: Noise Level	40° to 104°F < 65 dB(A)